

Instapacker[®] Tabletop Packaging System

Foam-in-Place

Simplified and
Efficient Premium
Protection



Instapacker® Tabletop Foam-In-Bag System

INSTAPACKER® TABLETOP SYSTEM FEATURES

- Produces up to 16 bags per minute.
- Adjust the amount of foam by simply pressing any one of 10 preset touch keys.
- Set a time delay of 3 or 6 seconds between bags.
- Option to run continuous bags.
- Compatible with all Instapak® foams.

HERE'S HOW IT WORKS

1. Press any one of the 10 preset foam amount keys to dispense a foam-filled bag. Remove the bag of expanding foam by tearing at the perforations.
2. The Instapak® foam-filled bag is placed into the carton and the product to be packaged is placed on top of the expanding bag.
3. A top cushion is formed by placing a second Instapak® foam-filled bag on top of the product and closing the carton.



PROVEN BENEFITS OF FOAM-IN-BAG PACKAGING WITH AN AFFORDABLE, USER-FRIENDLY INSTAPAK® SYSTEM.

Damage Reduction: Instapak® high-performance packaging foam is designed to protect your products during shipping, warehousing and general handling.

Fulfillment Velocity: Simplified touch-key control panel virtually eliminates the operator's learning curve and gets packages out the door faster.

Cube Optimization: The right amount of protective cushion, every time.

Customer Experience: A premium packaging presentation that avoids messy clean-up.

Optimize Warehouse Space: Small, innovative design saves valuable workspace. The system supports the packaging needs of shipping rooms, multiple pack stations and production environments.

AFFORDABLE PACKAGING AT THE TOUCH OF A BUTTON

With a minimal investment, the Instapacker® Tabletop foam-in-bag system will maximize your packaging productivity, reduce your material costs and increase customer satisfaction. With the simple touch of a button, operators can produce up to 16 foam-filled bags per minute, guided by easy-to-follow graphics on the touch-key control panel. To simplify handling, the Instapacker® Tabletop system utilizes two sizes of perforated film rolls with a fixed bag size: IP16 (19" x 16") and IP24 (19" x 24").

SPECIFICATIONS

Electrical
200-240 VAC Dedicated
Circuit, 30 Amp, Single-
Phase with equal voltage
from each leg to ground

Receptacle Type
NEMA L6-30R
UL and CE Approved

System Dimensions
(L x W x H)
19" x 19" x 28"

1-800-648-9093
SealedAir.com/product-care

@SealedAirPack

@SealedAirPack

Corporate Office: Sealed Air Corporation (US)
2415 Cascade Pointe Boulevard, Charlotte, NC 28208

www.sealedair.com

© 2016. Sealed Air Corporation. All Rights Reserved. Printed in the U.S.A. Instapacker®, and the Sealed Air & Trillian Design™ are trademarks of Sealed Air Corporation (US).