

ProPad™

Paper Cushioning System

Paper Cushioning
Has Never Been
Easier



ProPad™

Paper Cushioning System

Paper Cushioning
Has Never Been
Easier

THE SEALED AIR ADVANTAGE

The ProPad™ system provides unmatched peace of mind that comes from a rugged and dependable Sealed Air packaging system. The system requires minimal service and delivers greater uptime for a more profitable packaging operation.

TOUCH SCREEN OPERATION AND EASY LOADING

The ProPad™ system features an easy-to-use touch screen with four operation modes: Manual, Endless (batching), Auto Repeat (cut-and-hold), and Ordered (programmable sequence). In Manual Mode, creating pads is as simple as pushing a button or a foot pedal. In the Endless, Auto Repeat, or Ordered modes the system consistently delivers the desired pad size on demand in the manner that is most effective for your operation. The bottom-loading design creates fast material changeovers, getting you up and running in no time.

CREATE PAPER PACKAGING AT UNMATCHED SPEEDS

The ProPad™ system capitalizes on Swiss engineering to create custom-length paper pads, at speeds up to 150 per minute. This is the ideal solution for cushioning, blocking, and bracing.

EFFORTLESSLY INTEGRATE INTO YOUR CURRENT OPERATION

The ProPad™ system seamlessly integrates it into your current packaging operation. The system is ideal for a workstation, as TigerPad® material can be used straight from the system or batched into bins. The foot pedal and remote keypad make the system suitable for on-line operations. At half the weight and footprint of traditional paper packaging systems, the portable system is easy to position anywhere.

SEALED AIR SUSTAINABILITY

TigerPad® paper delivers superior protective performance while using less paper than other options. Our paper is made from 100% recycled fibers (85% post-industrial, 15% post-consumer) and can be reused or curb side recycled. The patented, single-motor design reduces power consumption and conserves energy.



SPECIFICATIONS

Weight (without material)

322 lb / 146kg

Overall Size (L x W x H)

86cm x 73cm x 150cm =
34" x 29" x 59"

Electrical

115 VAC, 50/60 Hz
Single Phase, 15A Service
230 VAC, 50 Hz,
Single Phase, 10A Service

Certifications

CE, TUV and PSE Approved

